

EL[®]MARK

The Brand of Electricity

RECESSED SPOTLIGHTS EL-6705 SERIES



GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 40W
- ∴ Driver: non-isolated driver
- ∴ Colour temperature: 3000K; 4000K; 6500K
- ∴ Colour body: White
- ∴ Material: Aluminium
- ∴ Beam angle: 90°
- ∴ CRI: Ra≥80
- ∴ Protection level against moisture and dust: IP44
- ∴ Dimming with DALI driver: 99DALI40105042 5IN1 DALI, Push function, 0-10V, PMW & RX dimming
- ∴ Dimming with 0-10V driver: 99SETDC40D010 with 0-10V dimming

FEATURES »

- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for shops, hotels, offices, showrooms halls, museums and restaurants.
- ∴ High degree of protection
- ∴ Lightweight construction


TECHNICAL SPECIFICATION SHEET

[PRODUCT DETAILS »](#)

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Cut hole (mm)	Colour body
92EL67054030/WH	40	3600	3000	220x130	white
92EL67054040/WH	40	3600	4000	220x130	white
92EL67054065/WH	40	3600	6500	220x130	white

[DIMENSIONS »](#)

Catalogue number	Length (mm)	Width (mm)	Height (mm)
92EL67054030/WH	230	145	85
92EL67054040/WH	230	145	85
92EL67054065/WH	230	145	85



[ADDITIONAL INFORMATION »](#)

Catalogue number	Barcode	Packing/Box (pcs)
92EL67054030/WH	3800131253101	1/10
92EL67054040/WH	3800131253118	1/10
92EL67054065/WH	3800131253125	1/10