

ELMARK[®]

The Brand of Electricity

TWO & FOUR LINES TRACK LIGHTS K30 SERIES



GENERAL INFORMATION »

- ∴ Input Voltage: 175-265V AC; 50/60 Hz
- ∴ LED Chip: OSRAM
- ∴ Colour body: Black
- ∴ Material: Aluminium
- ∴ Protection against dust and moisture: IP40
- ∴ Beam angle: 120°
- ∴ Color temperature: CCT- Settable:
3000/4000/5700K
- ∴ Life expectancy: 30000h
- ∴ High color rendering index: Ra> 80, which helps
for a more natural perception of colors in the
room.

FEATURES »

- ∴ Environmentally friendly - no mercury and lead
- ∴ Modern design
- ∴ Resistant to shock and vibration stable body
- ∴ Low heat emission

AREAS OF APPLICATION »

- ∴ Medical and cosmetic offices
- ∴ Workplaces
- ∴ Hotels
- ∴ Restaurants
- ∴ Showrooms
- ∴ Lighting at home

PRODUCT DETAILS »

Catalogue number	Type	Rail connectors	Watt (W)	Whole fixture lumens(Lm)	Colour temp. (K)
93K302L12CCT/BL	2 LINES	1	12	840	CCT- SETTABLE
93K302L24CCT/BL	2 LINES	2	24	1680	CCT- SETTABLE
93K302L48CCT/BL	2 LINES	2	48	3360	CCT- SETTABLE
93K304L12CCT/BL	4 LINES	1	12	840	CCT- SETTABLE
93K304L24CCT/BL	4 LINES	2	24	1680	CCT- SETTABLE
93K304L48CCT/BL	4 LINES	2	48	3360	CCT- SETTABLE
93K30S48CCT/BL	HANGING	2	48	3360	CCT- SETTABLE

DIMENSIONS »

Catalogue number	Length (mm)	Height (mm)	Width (mm)
93K302L12CCT/BL	281,5	127,7/71,7	42
93K302L24CCT/BL	562	127,7/71,7	42
93K302L48CCT/BL	1122	127,7/71,7	42
93K304L12CCT/BL	281,5	127,7/71,7	42
93K304L24CCT/BL	562	127,7/71,7	42
93K304L48CCT/BL	1122	127,7/71,7	42
93K30S48CCT/BL	1122	127,7/71,7	42

ADDITIONAL INFORMATION »

Catalogue number	Barcode	Packing/Box (pcs)
93K302L12CCT/BL	3800131239396	1/1
93K302L24CCT/BL	3800131239402	1/1
93K302L48CCT/BL	3800131239419	1/1
93K304L12CCT/BL		1/1
93K304L24CCT/BL		1/1
93K304L48CCT/BL		1/1
93K30S48CCT/BL	3800131239426	1/1

