


LAMP PHOTOMETRIC REPORT

MODEL: 93SS1040/BL		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 591.52 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1625	1644	1605	1537	1489	1491	1518	1580	0- 10	174.7	174.7	29.5
20	483.3	499.9	491.2	444.2	406.0	401.3	430.6	459.6	10- 20	259.4	434.1	73.4
30	122.6	115.3	114.4	104.6	105.1	92.41	92.68	107.3	20- 30	110.1	544.2	92
40	24.67	27.24	27.59	27.56	24.19	22.79	26.48	25.65	30- 40	34.03	578.3	97.8
50	5.218	5.651	6.182	4.897	4.222	4.332	4.189	5.067	40- 50	9.803	588.1	99.4
60	1.339	1.387	1.442	1.330	1.408	1.267	1.098	1.156	50- 60	2.213	590.3	99.8
70	0.4299	0.6415	0.9553	0.5104	1.096	1.156	0.4175	0.3990	60- 70	0.9395	591.2	99.9
80	0.0436	0.0354	0.0245	0.0327	0.0244	0.0368	0.0517	0.0327	70- 80	0.2877	591.5	100
90	0.0027	0.0014	0	0.0014	0.0163	0.0150	0.0163	0.0123	80- 90	0.0189	591.5	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:29 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```