


LAMP PHOTOMETRIC REPORT

MODEL: 99XLED621		
POWER: 24W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1755.4 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	571.2	570.2	570.3	570.8	571.9	572.8	573.3	572.6	0- 10	54.93	54.93	3.13
20	547.6	545.9	545.7	546.6	548.9	550.9	551.8	550.3	10- 20	158.8	213.7	12.2
30	508.1	505.5	505.2	506.4	509.9	512.9	514.3	511.9	20- 30	244.8	458.5	26.1
40	451.6	447.9	447.4	448.9	453.7	457.1	458.9	456.2	30- 40	302.4	760.9	43.3
50	375.4	370.2	369.0	370.6	377.0	379.8	382.4	379.8	40- 50	321.3	1082	61.7
60	278.1	272.4	270.8	271.5	278.0	280.5	283.7	281.7	50- 60	293.1	1375	78.4
70	170.7	167.5	165.7	165.4	169.8	173.3	175.9	174.1	60- 70	221.3	1597	91
80	71.91	69.89	66.52	66.76	69.90	71.82	74.43	71.87	70- 80	125.8	1722	98.1
90	1.317	1.076	1.555	1.078	0.9376	0.9482	0.9340	0.9187	80- 90	32.95	1755	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:09 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```